

HD16 - 16 LITRE MANUAL KNAPSACK SPRAYER



Phone : 01673 866677
 Fax : 01673 866699
 Email : info@mosskillers.co.uk
 Web : www.mosskillers.co.uk

**AGRICULTURE
 HORTICULTURE
 DUST DAMPING
 PEST CONTROL
 DISINFECTANTS
 INDUSTRIAL
 APPLICATIONS
 GARAGES**



**LIGHT WEIGHT!
 Weighs Just 3.4kgs(empty)**

Heavy Duty Trigger Valve:
 Easy to operate lever. Lever also locks for constant spraying, with in line filter

Reinforced Spray Lance:
 500mm long for optimum operating efficiency

Internal, High Efficiency Piston Pump:
 Long life chemical resistant seals. Operates with minimum effort. Safety valve prevents overloading

Carrying Handle:
 For easy transportation

Pumping Lever With Hand Grip:
 Can be mounted for left or right hand operation. Requires less pumping effort

Lance Holder Clips:
 To secure the lance for transportation and storage

High Pressure Hose:
 1800mm Long

Wide Filler Opening:
 Wide 115mm opening and deep basket strainer facilitate cleaning and quick filling. Tank lid has one-way breather valve to prevent leaking

16 Litre Ergonomically Designed Tank:
 Contoured for maximum comfort, impact, corrosion and UV resistant, high density polypropylene. Filling scale in gallons and litres

Built in Agitator:
 Internal agitator constantly mixes the chemical solutions

Comes With 3 Different Nozzles:
 Nozzle cap is compatible with any standard nozzle attachment fitted with nozzle filter

<p>Flow Calibrator Bottle: the easiest and fastest way to calibrate a knapsack sprayer reducing environmental waste and damage</p>	<p>Spray Hood: To prevent drift and avoid contact of non selective herbicides with the crop</p>	<p>Spray Lance 160: Mounted with 2 nozzles to improve penetration specially on perennial crops</p>	<p>Pliable Boom 3 Nozzles: Hold the required shape for better coverage of row crops</p>	<p>Double Nozzle Boom: Improves coverage increasing productivity</p>	<p>Extension 600: Increases the application reach on garden beds or high trees</p>
--	---	--	---	--	--

HD-16 has optional accessories for many herbicides, insecticides and fungicide applications

TECHNICAL SPECIFICATIONS	
PART NUMBER	OT192059
NET WEIGHT	3.4KGS
TANK CAPACITY	16 LITRES
DIMENSIONS	380 x 175 x 560mm
INSTALLED NOZZLE	ADJUSTABLE (blue)
FLOW RATE	615ml/min
PUMP TYPE	PISTON
WORKING PRESSURE	1-4 bar (15-60psi)
PACKING IN CARTON	42 x 21 x 57cm Weight 4.4kgs

Also Available: **DOUBLE NOZZLE HOLDER-** For high volume spraying
VPC-1 & 2 BAR CONSTANT PRESSURE VALVE - As fitted to the X-15 MODEL